






HWS

Built-in Speaker Multi Visual Light Bar.

- · Dome lens: Polycarbonate.
- · Speaker Cover / Chassis: Corrosion-resisting Aluminum.
- \cdot High performance miniature DC motor support economical 0.1-amp power consumption with operating temperature lowest at -40°C, and rated life at 10,000 hours.
- \cdot Total 360-degree light emission ensures outstanding visibility and safety.
- · New unitized speaker with high-volume sound output of 103dB/m.
- · The speaker is integrated into the chassis.
- · Easy mentenance: Adopted commonly used H1 Halogen lamp (12V55W / 24V70W).

Specification

Specification				
Model	HWS-12HM	HWS-24HM	HWS-12HD	HWS-24HD
Number of rotating light	Four rotating light		Two rotating light	
Rated Voltage	DC12V DC24V		DC12V	DC24V
				-
Operating Voltage range	DC9.5~15.0V	DC20.0~30.0 V	DC9.5~15.0V	DC20.0~30.0 V
Current Consumption	19.0A	10.8A	9.4A	5.4A
Illuminator	12V 55W x4	24V 70W x4	12V 55W x2	24V 70W x2
Luminosity	45,000cd(at 12.8V)	32,000cd(at 28.0V)	45,000cd(at 12.8V)	32,000cd(at 28.0V)
Operating temperature range	-30° C∼+75° C			
Vibration resistance	JIS D 1601 45GRADE (45m/s) [up and down:4h(33.3Hz),right and left:2h(33.3Hz),front and back:0.5h(31Hz) 1.5(33.3Hz)]			
Available speaker	100W x 1			
Power cord	VCT 1.25mm ² ×8 5,300mm			
Waterproof	SAE 575J			
Weight	approx. 16.0kg approx. 15.3kg			



SAP-100WB type

Electronic Siren Amplifier

- Four automatic sounds, selectable via a rotary switch, and two manual types:siren and horn.
- The accessory microphone is a high-performance, omnidirectional unit.
- Backlight indicators made for at-a-glance operation.

69.5

18

• Four automatic tunes, including the sound of a wail, yelp, high-low and yeow, and two sounds--air horn and siren are provided.



Note: Use speaker -- SPS-100A/DU-100A/SPU-100

Weight

1.95kg