

### Series 45/56 - OS&Y Gate Valve, UL/FM Approved

Body : Ductile Iron, ASTM A536  
 Working pressure : 250 psi (2-1/2" - 12"), 200 psi (14" - 16")  
 Flanged end : EN1092 PN 10/16 or ANSI B16.42 Class 150  
 Product from AVK Polska, Poland

**10 years warranty**

Size :  
 \*2", 2 1/2", 3",  
 4", 6", 8", 10",  
 12", 14", 16"  
 (\*minimum order required)



### Series 45/59 010 - NRS Gate Valve, UL/FM Approved

Body : Ductile Iron, ASTM A536  
 Working pressure : 250 psi (2-1/2" - 12"), 200 psi (14" - 16")  
 Flanged Ends : EN1092 PN 10/16 or ANSI B16.42 Class 150  
 Product from AVK Polska, Poland

**10 years warranty**

Size :  
 2 1/2", 3", 4",  
 6", 8", 10",  
 12", 14", 16"



### Series 45/59 020 - NRS Gate Valve, UL/FM Approved

Body : Ductile Iron, ASTM A536  
 Working pressure : 250 psi (2-1/2" - 12"), 200 psi (14" - 16")  
 Flanged Ends : EN1092 PN 10/16 or ANSI B16.42 Class 150  
 Product from AVK Polska, Poland

**10 years warranty**

Size :  
 2 1/2", 3", 4",  
 6", 8", 10",  
 12", 14", 16"



### Series 34/00 - Telescopic Indicator Post, UL/FM Approved

Post indicator bell : Ductile iron  
 Stem : Cold drawn steel  
 Lower barrel : PVC pipe  
 Target sign : Aluminum (painted)  
 Window : Polycarbonate  
 UL Listed : 4" - 16". FM Approved : 4" - 14"  
 Product from AVK Polska, Poland

**10 years warranty**

Size :  
 3", 4",  
 6", 8", 10",  
 12", 14", 16"



### Series 34/80 - Wall Indicator Post, UL/FM Approved

Post indicator bell : Ductile Iron  
 Target sign : Aluminum (painted)  
 Window : Polycarbonate  
 UL Listed : 4" - 16". FM Approved : 4" - 14"  
 Product from AVK Polska, Poland

**10 years warranty**

Size :  
 3", 4",  
 6", 8", 10",  
 12", 14", 16"



### Series EVFS (75/41)- Butterfly Valve (Flanged), FM Approved

Body : Ductile Iron ASTM A 395  
 Design Standard : En593 and API 609  
 End Connection : EN 1092 PN 10/1, ASME B16.5 cl.150  
 Face to face : EN 588-1/2, API 609A  
 Disc : Centric Design (SS, Duplex, Aluminum Bronze)  
 Shaft : Dry shaft design (SS, Duplex)  
 Product from Wouter Witzel, Netherlands

**5 years warranty**

Size :  
 2 1/2", 3", 4",  
 5", 6", 8", 10",  
 12", 14", 16"



### Series 24/92 - Wet Barrel Hydrant, UL/FM Approved

Body : Ductile Iron  
 Working pressure : 250 psi  
 Product from American AVK, USA

**10 years warranty**

Size :  
 1P, 2H  
 1P, 1H  
 2P, 1H



### Series 24/10 - Wet Barrel Hydrant w/ monitor connection, UL/FM Approved

Body : Ductile Iron  
 Working pressure : 200 psi  
 w/ monitor flange 4" to ANSI cl. 150  
 Product from AVK Saudi, Saudi Arabia

**2 years warranty**

Size :  
 1P, 2H



### Series 24/5X - Wet Barrel Hydrant, UL Listed

Body : Stainless Steel  
 Working pressure : 200 psi  
 Product from American AVK, USA

**1 years warranty**

Size :  
 1P, 2H  
 1P, 1H (on request)  
 2P, 1H (on request)



### Series 145 - OS&Y Gate Valve (Light version), UL/FM Approved

Body : Ductile Iron, ASTM A536  
 Working pressure : 250 psi (2-1/2" - 8")  
 Flanged end ANSI B16.42 Class 150  
 Product from American AVK, USA

**2 years warranty**

Size :  
 2 1/2", 3",  
 4", 6", 8"



### Series 815 - Butterfly Valve, UL/FM Approved

Body : Ductile Iron, ASTM A536  
 Working pressure : 300 psi (2-1/2" - 8")  
 Connection : Groove  
 Product from American AVK, USA

**1 year warranty**

Size :  
 2 1/2", 3",  
 4", 6", 8"







# FIRE PROTECTION NON-UL/FM



### Series 21/46 - OS&Y Gate Valve NON-UL/FM

Body : Ductile Iron, GGG-50  
Working pressure : 16 bar  
Flanged end : EN1092-2 PN 10/16  
Face to face according to EN558 table 2 series 3  
Standard coating color **BLUE**  
\*Available External epoxy coating to RAL3000 (RED)  
Product from AVK Malaysia

**10 years warranty**

Size :  
2", 2 1/2", 3",  
4", 5", 6",  
8", 10", 12",  
14", 16"



### Series 910/21 - Y-Strainer, Non-UL/FM

Body : Ductile Iron, GJS-450  
Working pressure : 16 bar  
Flanged Ends : EN1092-2 PN 10/16  
Standard coating color **BLUE**  
\*Available External epoxy coating to RAL3000 (RED)  
Product from AVK Malaysia

**2 years warranty**

Size :  
2", 2 1/2", 3", 4", 5",  
6", 8", 10", 12"



### Series 21/36 - NRS Gate Valve NON-UL/FM (Light Version)

Body : Ductile Iron, GGG-50  
Working pressure : 16 bar  
Flanged Ends : EN1092-2 PN 10/16  
Standard coating color **BLUE**  
\*Available External epoxy coating to RAL 3000 (RED)  
c/w stem cap  
Product from AVK Malaysia

**10 years warranty**

Size :  
3", 4",  
6", 8"



### Series 24/88X - Flow Guard II, Bi-Directional Check Valve, Non-UL/FM

Body : Ductile Iron  
Working pressure : 250 psi  
Prevents excessive water loss in an automobile collision  
Head loss at 1,000 gpm is < 2.5 psi  
Product from American AVK, USA

**10 years warranty**

Size :  
6"



### Series 21/50 - NRS Gate Valve NON-UL/FM

Body : Ductile Iron, GGG-50  
Working pressure : 16 bar  
Flanged Ends : EN1092-2 PN 10/16  
Standard coating color **BLUE**  
\*Available External epoxy coating to RAL 3000 (RED)  
c/w stem cap  
Product from AVK Malaysia

**10 years warranty**

Size :  
2", 10", 12",  
14", 16"



### Series 24/6X - Wet Barrel Hydrant, Non-UL/FM

Body : Bronze  
Working pressure : 200 psi  
For seawater application  
Product from American AVK, USA

**1 years warranty**

Size :  
1P, 2H  
1P, 1H (on request)  
2P, 1H (on request)



### Series 24/80 - Breakable Flange for Wet Barrel Hydrant, Non-UL/FM

Body : Ductile Iron  
Prevents excessive wet hydrant damage in an automobile collision  
Product from American AVK, USA

Size :  
6"



### Series 41/X1 (X 2/6) - Resilient Seat Swing Check Valve NON-UL/FM

Body : Ductile Iron, GGG-50  
Working pressure : 16 bar  
Flanged Ends : EN1092-2 PN 10/16  
Without lever/weight  
Standard coating color **BLUE**  
\*Available External epoxy coating to RAL3000 (RED)  
Product from AVK Malaysia

**10 years warranty**

Size :  
2", 2 1/2", 3",  
4", 5", 6",  
8", 10", 12"



The specifications and designs of the products are subject to change without prior notice for the purpose of improvement of the products

Dealer :

