



# TOHATSU

## PORTABLE FIRE PUMPS

### VE1500W

- 2050 lt/min @ 0.6 Mpa (6 Bar)
- 1800 lt/min @ 0.8 Mpa (8 Bar)
- 1500 lt/min @ 1.0 Mpa (10 Bar)

- Suction Performance  
(The best suction performance in the industry (9m/30ft))
- Light Weight
- Comfortable Operation
- Electric Fuel Injection - EFI System  
(ECU control the ideal fuel supply and optimizes spark-timing where engine-condition varies, Resulting better fuel economy than carburetor, stable operation and smooth)



- Cooling system : Water Cooled
- Displacement : 804cc (49.0 cu in)
- Output : 44kW (60PS)
- Starting System : Electric and Manual
- Fuel Tank Capacity : 24 Lit (6.34 gal)
- Fuel Consumption : 22 Lit / Hr (5.81 gal / Hr)
- Suction System : 4 Blade Rotary Vane Vacuum Pump (Oil-less type)
- Thread on Suction : BSP 4 inch, JIS 3 1/2 inch
- Thread on Discharge : BSP 2 1/2 inch, JIS 2 1/2 inch
- Discharge Valve : Flat Valve
- Pump Performance : 2050 Lit / min at 0.6 Mpa  
(Suction Height:3m) 1800 Lit / min at 0.8 Mpa  
1500 Lit / min at 1.0 Mpa
- Max. Suction Height : 9 meter
- Dimension : 748 x 732 x 827 mm
- Dry Weight : 104 kg
- Operation Weight : 124 kg

#### AUTHORIZED DISTRIBUTOR AND SERVICE CENTER :

PT. SABERINDO PACIFIC  
 Kompleks Mega Grosir Cempaka Mas  
 Blok J No. 10 Jl. Letjend. Suprpto, Jakarta 10640  
 Jakarta - Indonesia  
 Telp : +62 21 4288 8282 (Hunting)  
 Fax : +62 21 4287 2323  
 Website : [www.saberindo.co.id](http://www.saberindo.co.id)  
 Email : [info@saberindo.co.id](mailto:info@saberindo.co.id)



#### Performance Curve

